

EBS Application Object Library (AOL)

No.	Views	Description
1	AOL_Columns	This view returns information about individual columns in application tables, consistent with the technical reference manual. Also returned is information on whether this column is related to a flexfield, and other values identifying the flexfield that is using the table column and the value set to which this column belongs.
2	AOL_Common_Quickpicks	This view returns shared QuickCodes that are used by Oracle Applications for QuickPicks. Each row includes an application identifier, a QuickCode type, the QuickCode, and the meaning of the QuickCode.
3	AOL_Conc_Manager_Rules	Information about Concurrent Managers and their specialization rules. Included are application identifier, a complex rule for each identifier, and the name of the complex rule.
4	AOL_Conc_Pgm_Executables	This view returns information about concurrent programs. Each row includes a name and description of the concurrent program. Each row also includes the execution methods for the program, the argument method, and whether the program is constrained.
5	AOL_Conc_Request_Args	This view returns information about the arguments or parameters for pending and completed concurrent requests. This view has arguments 26 through 100 available and the request identifier.
6	AOL_Concurrent_Programs	This view returns information about concurrent programs. Each row includes a name and description of the concurrent program. Each row also includes the execution methods for the program, the argument method, and whether the program is constrained.

No.	Views	Description
7	AOL_Concurrent_Requests	This view returns historical information about pending and completed concurrent requests and their parameters, such as who submitted, the request type, whether the request should run sequentially with other requests in the same logical database or instance.
8	AOL_Currencies	This view stores information about currencies. Each row includes the Currency_Code established by ISO (International Standards Organization) standard, the name of the Currency, an Enabled_Flag to indicate whether the Currency is enabled for use at your site, a Currency_Flag to indicate if this is a Currency or a statistical unit, and Issuing_Territory_Code which indicates the issuing country. Issuing_Territory_Description and Issuing_Territory_Short_Name are listed too.
9	AOL_Descr_Flex_Segments	Basic information about descriptive flexfields. This view only returns information about table related descriptive flexfields that have actually been defined, Standard Report Submission descriptive flexfields are not available here.
10	AOL_Descr_Flexfields	Basic information about all table related descriptive flexfields is available. All possible table related descriptive flexfields are returned, even if no segments are actually defined for the flexfield.
11	AOL_Exclusive_Conc_Pgms	This view returns information about incompatible concurrent programs. This means that the programs cannot run at the same time. Each row identifies a concurrent program and another concurrent program that is incompatible with it.
12	AOL_Flex_Cross_Val_Rules	This view returns information about key flexfield cross-validation rules. Each row includes values that identify the application with which the key flexfield is registered, the

No.	Views	Description
		key flexfield structure, and the name and description of the cross-validation rule.
13	AOL_Flex_Hierarchies	This view stores information about flexfield hierarchies. Each row includes a value set identifier and name, a hierarchy identifier, and a hierarchy name. One row is returned for each flexfield hierarchy. Oracle Applications use this information to build and process multi-level hierarchies of flexfield data.
14	AOL_Flex_Val_Hierarchies	This view returns information about child value ranges for key flexfield segment values. Each row includes an identification of the parent value the range belongs to, as well as the low and high values that make up the range of child values.
15	AOL_Flex_Val_Qualifiers	This view returns information about flexfield and segment qualifiers. A flexfield qualifier describes segments defined when customizing key flexfields. Each row includes a key flexfield code, a flexfield qualifier, a segment qualifier, and the date these qualifiers were assigned to the flexfield. One row is returned for each qualifier assignment.
16	AOL_Flex_Value_Security	This view returns information about key flexfield value security rules. Each row includes the security rule's name and description, as well as the Error_Message a user sees after entering a value that violates the rule.
17	AOL_Foreign_Keys	This view returns information about the registered foreign keys in your applications. Each row includes the name and description of the foreign key, the primary key it references, the cascade behavior, the relation, and any special condition.
18	AOL_Forms	This view returns information about your registered application forms. Each row includes the form's file name, the EasyForm

No.	Views	Description
		title, and a description of the form.
19	AOL_GL_Security	This view returns the accounting flexfield value security rules associated with each user and responsibility. The view lists the details of the value rule including the Segment_Name and the ranges of included or excluded values.
20	AOL_Index_Columns	This view returns information about individual columns in the Application indexes. Each row includes the index column and its sequence in the index.
21	AOL_Indexes	This view returns information about the registered indexes in Oracle Applications. Each row includes the name and description of the index, information about the storage parameters for the index and an Auto_Size flag which indicates whether the install should automatically apply a sizing factor to the storage parameters.
22	AOL_Languages	This view returns information regarding national dialects. The territory is also available for each available dialect.
23	AOL_Lov_All_Currencies	For version 10.7 - 10.9999, This view is used to select the CURRENCY_CODE and NAME from FND_CURRENCIES. For version 11+, This view is used to select the CURRENCY_CODE and NAME from FND_CURRENCIES_TL. This LOV was designed to work with Answers.
24	AOL_Lov_Amounts	This view selects expression 0 from n_application_owners where rownum = 1.
25	AOL_Lov_Application_Names	For version 9.0 - 10.9999, This view is used to select the APPLICATION_NAME from FND_APPLICATION. For version 11+, This view is used to select the APPLICATION_NAME from N_FND_APPLICATION_VL. This LOV was designed to work with Answers.
26	AOL_Lov_Conc_Request_Ids	This view is used to select the REQUEST_ID

No.	Views	Description
		from FND_CONCURRENT_REQUESTS. This LOV was designed to work with Answers.
27	AOL_Lov_Dates	This view selects expression sysdate from n_application_owners where rownum = 1.
28	AOL_Lov_Desc_Flexfield_Names	For version 10.7 - 10.9999, This view is used to select the DESCRIPTIVE_FLEXFIELD_NAME from FND_DESCR_FLEX_COLUMN_USAGES. For version 11+, This view is used to select the DESCRIPTIVE_FLEXFIELD_NAME from N_FND_DESCR_FLEX_COL_USAGE_VL. This LOV was designed to work with Answers.
29	AOL_Lov_Id_Flexfield_Names	In query 1, for version 10.7 - 11.4999, This view is used to select the PRINTER_NAME from FND_PRINTER. For version 11.5+, This view is used to select the PRINTER_NAME from N_FND_PRINTER_VL. In query 2, for version 11+, this view is used to gather general printer information.
30	AOL_Lov_Printer_Names	In query 1, for version 10.7 - 11.4999, This view is used to select the PRINTER_NAME from FND_PRINTER. For version 11.5+, This view is used to select the PRINTER_NAME from N_FND_PRINTER_VL. In query 2, for version 11+, this view is used to gather general printer information.
31	AOL_Lov_Users	This view is used to select the USER_NAME from FND_USERS. This LOV was designed to work with Answers.
32	AOL_Lov_Y_N_Flags	This view is used to select the LOOKUP_CODE for YES/NO values from FND_LOOKUP_VALUES. This LOV was designed to work with Answers.
33	AOL_Menus	This view returns information about defined menus. Oracle and site specific menus are returned, as well as detailed information about submenus, macros, forms, and subroutines.

No.	Views	Description
34	AOL_Printer_Drivers	This view returns information about printer drivers and subroutines that are defined with Oracle Application Object Library. Each row includes a driver name, user driver name or title for the driver, an optional platform code, and the initialization and reset strings that are used to format printers.
35	AOL_Printer_Information	This view returns information about all the printers that are defined with Oracle Application Object Library. Each row includes a printer type, a print style, and the name of the printer driver.
36	AOL_Profile_Options	This view returns information about user profile options. Each row includes the actual profile option name, the more descriptive end-user name, and a description of the profile option.
37	AOL_Request_Groups	This view returns information about report security groups. Each row includes a value identifying a report security group, the name of a report security group, the group code, and a description of the report security group. One row is returned for each report security group you defined in the Define Report Group form.
38	AOL_Responsibility	This view returns information about responsibilities. Each row includes the name and description of the responsibility, the application it belongs to, and values that identify the main menu and the first form that it uses.
39	AOL_Shorthand_Flex_Alias	This view returns alias information for shorthand flexfield entry. This capability provides users with a quick way to enter key flexfield data in Oracle applications. Each row includes the name and description of the shorthand alias, as well as values that identify the key flexfield structure to which the alias belongs.

No.	Views	Description
40	AOL_Tables	This view returns information about the registered tables in the Applications. Each row includes Table_Name, Application_Name, User_Table_Name (title), and a Description.
41	AOL_User_Logins	Information about user logins and forms that they have accessed. This view only returns information for users whose Signon Audit level has been set at the User level or higher. Responsibility information is only returned if the Signon Audit Level is set to 'Responsibility' or higher for a particular user.
42	AOL_User_Responsibility	Basic information about Users and their Responsibilities as defined to Application Object Library. Each row includes the username (what a user types in at the sign-on screen) and information on when the user should change the password. Each row also contains information on when the user last signed on, start and end dates for when a username is valid and a description of the user.
43	AOL_Users	Basic information about Users. Each row includes the username (what a user types in at the sign-on screen) and information on when the user should change the password. Each row also contains information on when the user last signed on, start and end dates for when a username is valid and a description of the user.